

General Guidelines IVC Studio Moods

BEYOND
FLOORING



Storage & transport

Cartons should be stored and transported on a flat surface in neat stacks, always store the cartons flat and never put them on-end. Do not store the cartons in very cold (less than 2C°) or very warm (more than 40°C) or humid places.

Prior to installation

Visual inspection

Please inspect product prior to installation. Check that the colours correspond to those ordered, the quantities are correct and there is no visible damage to the boxes. Check the vinyl planks or tiles during installation for any visible defects. Do not install any planks or tiles that display any imperfections.

We recommend that you always use materials from a single production batch for each installation, as we cannot guarantee a shade match between different batches.

National regulations:

Site conditions and installation must always comply with the relevant national regulations and installation standards.

Suitability

- IVC Studio Moods can be laid on concrete, cementitious screed, anhydrite (calcium sulphate), timber, plywood, particleboard and ceramic tiles, which have been suitably prepared (see Floor Preparation).
- IVC Studio Moods can be used with traditional water based underfloor heating and cooling systems. Electric wire systems are not recommended unless the system is encased in a minimum of 9mm of suitable levelling compound. Direct contact with wired heating systems must be avoided. If in doubt seek further advice.
- IVC Studio Moods is only suitable for indoor installation.
- Seasonal temperature conditions: IVC Studio Moods can be used in any indoor situation, such as temperature controlled conservatories and holiday homes. Keep under all conditions the temperature between 6C° and 35C°. Avoid rapid temperature increases of more than 5C° per 12 hours.
- For commercial applications where roller castor chairs or heavy rolling loads are to be used we strongly recommend the use of IVC Studio Moods. However, if you do want to use IVC Studio Moods, please contact the IVC Technical Support Team.

Composition, construction and quality of the subfloor

Knowledge of the composition and construction provides valuable information that allows you to correctly check the acceptable humidity, compressive and tensile strength of the subfloor. In addition it tells you what type of floor preparation, levelling compound, and possible moisture barrier you may need during the installation process. When there is ambiguity or doubt about the quality or composition of your subfloor check with your floor preparation, levelling compound manufacturer/supplier.

Subfloor preparation

Irregularities in the subfloor

Good preparation is essential for trouble-free installation. It is vital for an excellent IVC Studio Moods finish. The appearance of IVC Studio Moods will only be as good as the quality of the base over which it is installed. Any irregularities in the subfloor will show through the finished floor and must be suitably prepared before installation.

The subfloor must be hard, smooth, clean and dry, as well as being free from defects and fit for purpose. When required, scrape off and remove old adhesives and loose laying levelling compound. Make sure the subfloor is flat and free from chemical substances and other contamination.

Unevenness of the subfloor may not be greater than 2mm measured over a width of 200cm.

A suitable plywood/levelling compound should be selected to ensure that no irregularities show through to the surface of the finished floor. However, the selection of suitable materials, including plywood, smoothing/levelling compounds and any ancillary products, is dependent upon the occupational use of the area and must be agreed by the supplier of the preparative materials and the flooring contractor. All floor preparation materials used must be used in accordance with the manufacturer's recommendations and in accordance with the national standards for resilient floorcoverings.

The moisture content of the subfloor

- Unheated cementitious screeds less than 2.0CM% - 75% RH (UK)
- Underfloor heated cementitious screeds less than 1.8CM% - 75% RH (UK)

- Unheated anhydrite (calcium sulphate) screeds less than 0.5CM%
- Underfloor heated anhydrite (calcium sulphate) less than 0.3CM%

Direct-to-earth concrete and stone subfloors must have an effective damp proof membrane (DPM) in accordance with the national standards for the installation of resilient floorcoverings. Follow manufacturer's detailed instructions for the installation of a surface applied DPM and the use of levelling compound. An overview of recommended manufacturers and suppliers can be provided by IVC.



Important

Floor installation should not begin until the installer has assessed and approved the subfloor and installation conditions


Acclimatisation

IVC Studio Moods must acclimatise in the room of installation, or an equivalent area for at least 24 hours prior to installation, or until such time as the product has achieved an ambient temperature. Again, this is a minimum temperature of 18°C and a maximum of 27°C.

- Unpack the IVC Studio Moods and check all planks or tiles in daylight for possible defects or discrepancies in colour.
- Stack the plank or tiles in straight piles away from heating, cooling or windows with direct intense sunlight. This is to achieve a gradual acclimatisation.

Temperature condition before installation

IVC Studio Moods should be installed with a room temperature of between 18°C and 27°C and a floor temperature of above 15°C.



Installations in areas colder than recommended will influence the installation properties of IVC Studio Moods. The planks or tiles will be less flexible, cutting will be harder and small pieces difficult to cut out. The lower the temperature, the more difficult the installation. For installation in areas warmer than recommended, we advise consultation with your local retailer/ installer on how to create the appropriate installation conditions.

Starting installation

Temperature condition during installation

A constant temperature, fluctuating no more than 5°C per day, not below the required 18°C room temperature and 15°C subfloor temperature, should be maintained 24 hours before, during and 72 hours after installation.

Underfloor heating

IVC Studio Moods can be used with traditional water based underfloor heating systems, provided there is a constant room temperature of 18°C for the acclimatisation period, installation and for 72 hours after installation. 24 hours after installation the underfloor heating must be gradually increased by increments of 5°C per day until it reaches the standard operating temperature conditions, with a maximum operating temperature of 27°C. For the suitability of the system please check the manufacturer's instructions.

Underfloor cooling

IVC Studio Moods can also be installed over floor cooling systems. However, the supply temperature of the cooling water must not be reduced below the dew point temperature. Temperatures below this point will produce condensation and can therefore damage the floor covering. Thermostats in the room must never be set at a temperature which is more than 5°C lower than the room temperature.

Recommended adhesives

Please seek further advice regarding IVC Accessories Adhesives or IVC approved adhesives for your country. Adhesive recommendations may differ by country or continent due to the composition of the adhesive, local climatic conditions and national installation regulations/standards.

For any special conditions, including installation suitability, underfloor heating and specific adhesive selection, please contact the IVC Technical team.

Recommended underlay

IVC Accessories™ Flex Pro: Heavy Duty Use

- Improved sound insulation ($\Delta L_w=10$ dB with 2.5 mm)
- Protective foil and pressure sensitive adhesive film for easy installation.
- Suitable for underfloor heating and cooling
- Provides excellent dimensional stability
- Suitable for Roller Castor Chairs & rolling loads up to 250kg

IVC Accessories Flex Pro can smooth out small irregularities of a maximum 5mm wide and 2mm deep. This allows for installation over existing floor coverings, such as ceramic tiles, linoleum, compact PVC floors and wooden floorboards.

LVT installed on IVC Accessories Pro is a “floating” floor. Therefore, a 3mm expansion gap must be incorporated at the perimeter of the room/area. For smart solutions to cover the expansion gap, see ‘finishing your floor’.



For the installation of IVC Accessories Flex Pro: lay the sheets butted, edge-to-edge, at a 90 angle to the laying direction of the new floorcovering. IVC Accessories Base and IVC Accessories Flex-Pro is to be laid PET Film side up and IVC Accessories Silent is to be laid anti-slip side up. There is no need to fix one sheet to another. A section at a time, separate the PET-film from the underlay sheet and

begin laying your new floor according to the fitting instructions. Do not use primer or other adhesive.

Installation step by step

Important:

The positioning of the pattern across the length and width can vary. Measure and calculate the area carefully and decide in advance the correct centre- and/or reference lines. It is visually best when there is an equal pattern left and right, front and rear of the design in the main room/area.

1. Determine the installation direction of the IVC flooring. Calculate how the partition of plank or tiles will be across the width of the room/area and mark a 100% straight line on the floor.
2. Highlight the second line so creating the section (for example, 5 rows wide) to be glued with the correct type of adhesive. Prior to using the adhesive read the manufacturer's instructions.
3. Spread the right amount of adhesive evenly over the subfloor and let it tack-off (open time) until it reaches its initial bonding strength. For more information consult the specifications of the adhesive being used and the IVC bonding PVC floor instructions.
4. Lay the planks or tiles, observing the direction of the arrows of the backing, into the tacked-off adhesive, in order to transfer the adhesive fully onto the backing (working time).

5. Cut the planks or tiles, free of tension, against the wall or skirting.
6. Do not spread adhesive on a section greater than can be processed within the working time.
7. To ensure full contact with adhesive, immediately press every plank or tile with a rubbing block or hand roller.
8. Wipe excess adhesive with a damp cloth.
9. Immediately roll each section with a (minimum) 50kg flooring roller. Roll several times, in different direction, during the adhesive working time.
10. Repeat steps 3 to 9 until the entire installation is completed.

Protection

IVC Studio Moods should be protected from heavy traffic for 72 hours after installation so that the tiles and adhesive can stabilise at constant temperature between 18-27°C.

First contact with water

Prevent the floor from coming into contact with water for the first 72 hours after installation. Hereafter the adhesive is sufficiently resistant to water so that the bonding strength will not be affected.



Recommended tools:

- Tape measure
- Pencil
- Chalk line
- Adhesive and trowel
- Damp cloth
- Set Square
- Utility knife
- Hand roller
- Roller minimum 50kg



Note:

An undulating substrate can cause slight gapping of the design planks or tiles during installation. IVC Studio Moods can be finished with IVC Accessories joint sealant; this will fill small gaps/ joints and close the entire surface so that no dirt or moisture can ingress the joints.

Overview IVC Studio Moods designs


Basket Weave Block




Basket Weave Small




Herringbone Small



Chevron Basic




Chevron Columns







Triangle





Hexagon



Honeycomb



Diamond




Step by step installation instructions for BASKET WEAVE BLOCK

Design



Recommended installation sequence




Step 1

Measure precisely the length and the width of the subfloor and determine the centre lines in the middle.

Step 2

Mark two reference lines on the subfloor at the position of the left and right sides of the first length row and the first width row and use it as a guide for the installation.



1 = centre lines
2 = reference lines

Step 3

Spread the adhesive on the subfloor in a small area which can be processed within the recommended installation method.

Step 4

Install the first length row in a straight line, according to the numbering specified.


Install the closing edges last but before the start of a new row.

Step 5


Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.

Step 6


Install all the other rows in the same way.




Examples of even or uneven numbers of patterns in the width and/or length of the area




Even numbers of pattern in the width



Even numbers of pattern in the length




Uneven numbers of pattern in the width



Uneven numbers of pattern in the length

Step by step installation instructions for BASKET WEAVE SMALL

Design



Recommended installation sequence


| | | | |
|----|----|----|----|
| 17 | 18 | 19 | 20 |
| 5 | | | |
| 1 | 2 | 3 | 4 |
| 6 | | | |
| 7 | 8 | 9 | 10 |
| 11 | | | |
| 12 | 13 | 14 | 15 |
| 16 | | | |

Step 1

Measure precisely the length and the width of the subfloor and determine the centre lines in the middle.

Step 2


Mark two reference lines on the subfloor at the position of the left and right sides of the first length row and the first width row and use it as a guide for the installation.



1 = centre lines
2 = reference lines

Step 3

Spread the adhesive on the subfloor in a small area which can be processed within the recommended installation method.



Step 4

Install the first length row in a straight line, according to the numbering specified.

Install the closing edges last but before the start of a new row.


Step 5

Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.


Step 6

Install all the other rows in the same way.


Examples of even or uneven numbers of patterns in the width and/or length of the area




Even numbers of pattern in the width



Even numbers of pattern in the length



Uneven numbers of pattern in the width



Uneven numbers of pattern in the length


Step by step installation instructions for HERRINGBONE SMALL

Design




Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle.




Step 2




The centre line always runs through the middle of the short side of the plank.

Step 3




Place a support surface (with a perfect angle of 90 °) at 45 ° so that the centre line runs through the centre of the top plank.

Step 4



You can now draw 2 guiding lines that mark the area in which you are going to install on Flexpro, or between which you will apply the glue.


Step 5



Now install the planks in the order as indicated above in a V shape. Always press well on the long side to

ensure that the 90 ° angle is maintained. Complete this line to the end of the room.

Step 6




Now start on the other side and first of all install your supporting surface (with a perfect angle of 90 °) in 45°. Now place half of the V shape and work in the other direction. Always press well on the long side to be sure that the 90 ° angle is maintained. Complete this line to the end of the room. You can do this left and right at the same time.

Step 7


Now assemble all subsequent rows in the same way.

Step by step installation instructions for CHEVRON BASIC

Design



Recommended installation sequence




Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle.

Step 2

Mark three reference lines on the subfloor at the end position of the left and right sides of the first two rows and a 45 degree on the cross centre line and use it as a guide for the installation.



1 = centre line
2 = reference lines


Step 3

Spread the adhesive on the subfloor within the reference lines and install according to the recommended installation method.

Step 4

Install the first two rows simultaneously, according to the numbering specified.

Install the closing edges last but before the start of a new row.




Step 5

Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.


Step 6

Install all the other rows in the same way.




Examples of even or uneven numbers of patterns in the width and/or length of the area

Even numbers of pattern in the width




Uneven numbers of pattern in the width



Step by step installation instructions for CHEVRON COLUMNS

Design




1 = centre line
2 = reference lines

Step 3

Spread the adhesive on the subfloor within the reference lines and install according to the recommended installation method.

Recommended installation sequence




Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle.

Step 2

Mark two reference lines on the subfloor at the end position of the left and right sides of the first two rows and use it as a guide for the installation.



Step 4

Install the first two rows simultaneously, according to the numbering specified.


Install the closing edges last but before the start of a new row.

Step 5

Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.


Step 6

Install all the other rows in the same way.




Examples of even or uneven numbers of patterns in the width and/or length of the area

Even numbers of pattern in the width




uneven numbers of pattern in the width




Step by step installation instructions for TRIANGLE

Design




Start always in the middle so that the closing edges are equal divided



Step 1

Measure precisely the length and the width of the subfloor and determine the centre lines in the middle.

Use if you wish the reference paper



Step 2

Mark two reference lines on the subfloor at the end position of the front and rear sides of the first row and use it as a guide for the installation.

1 = centre lines
2 = reference lines

Step 3

Spread the adhesive on the subfloor within the reference lines and install


according to the recommended installation method.

Step 4


Install the first row according to the numbering specified.

Install the closing edges last but before the start of a new row.

First numbers



Continuation



Step 5


Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.

Step 6


Install the rest of the floor in the same way.

Step by step installation instructions for HEXAGONS

Design



Start always in the middle so that the closing edges are equal divided




Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle. Use if you wish the reference paper.

Step 2

Mark two reference lines on the subfloor at the end position of the left and right sides of the first row and use it as a guide for the installation.



1 = centre lines
2 = reference lines

Step 3


Spread the adhesive on the subfloor for at least three rows and install according to the recommended sequence.

Step 4

Install the first fase simultaneously, according to the numbering specified.

Install the closing edges last but before the start of a new row.

First numbers



Continuation



Step 5


Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.

Step 6

Install the rest of the floor in the same way.

Step by step installation instructions for HONEYCOMB

Design




Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle. Use if you wish the reference paper.

Step 2

Mark two reference lines on the subfloor at the end position of the left and right sides of the first row and use it as a guide for the installation.



1 = center lines
2 = reference lines


Step 3

Spread the adhesive on the subfloor for at least three rows and install according to the recommended sequence.

Step 4

Install the first three rows simultaneously, according to the numbering specified.

Install the closing edges last but before the start of a new row.



Step 5


Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.

Step 6


Install all the other rows in the same way.

Examples of even or uneven numbers of patterns in the width and/or length of the area

Even numbers of pattern in the width




Uneven numbers of pattern in the width




Step by step installation instructions for DIAMOND

Design




Start always in the middle so that the closing edges are equal divided



Step 1

Measure precisely the width of the subfloor and determine the centre line in the middle. Use if you wish the reference paper.



Step 2

Mark two reference lines on the subfloor at the end position of the left and right sides of the first row and use it as a guide for the installation.

1 = centre lines
2 = reference lines


Step 3

Spread the adhesive on the subfloor for at least three rows and install according to the recommended sequence.

Step 4

Install the first few rows simultaneously, according to the numbering specified.

Install the closing edges last but before the start of a new row.



Step 5

Divide the adhesive on the subfloor for the next one or more rows and install the rows according to the previous method.

Step 6

Install all the other rows in the same way.

Finishing your floor

IVC Accessories offers a range of smart flooring solutions to your finishing needs. The offer combines unique functionality with style: a hardwearing solution that ensures smooth transitions at all times.

How to finish your floor at the wall

1. IVC Accessories standard skirting: the perfect transition

- The identical connection for your IVC Studio Moods floor
- Water-resistant
- Wear-resistant
- Perfect water-resistant corner solution



2. IVC Accessories paintable skirtings: style by choice

- Unique water-resistant material
- Colour coordinate your pre-primed skirting boards & walls
- Use our renovation skirting on top of existing skirting boards



How to connect your floor with higher or lower level floor surfaces

IVC Accessories Multifunctional profile

- Sleek aluminium profile for a minimalistic design that lends a smart and modern look
- Connect the floor with any other type of higher or lower lying floor surface, with a height difference up to 12.3mm



How to fill small joints to perfectly finish your floor and to protect it from dirt & moisture

IVC Accessories joint sealant:

- Specially developed for LVT
- Available in different colours to perfectly match the floor



⇒ For specific installation instructions on IVC
Accessories skirting, profiles and nosings, please
consult www.ivc-commercial.com

Maintaining your floor

Appropriate maintenance procedures will help to preserve the appearance and will extend the life of a IVC. The frequency of maintenance will depend on the amount and type of traffic, degree of soiling, the floor colour and type. IVC have a Protectonite-PU lacquer on top of the resistant wear layer. This lacquer protects against soiling and makes overall maintenance easier. Protectonite also makes any post-treatment with protection polish unnecessary.

External conditions

The appropriate management of external conditions can help to protect the flooring, which saves time and expenses on cleaning and maintenance, and also extends its lifespan. Most soiling comes from an external source and is transported indoors by foot and rolling traffic. If dirt lodges under sliding furniture, the flooring will not only be soiled but will also suffer (light) damage in the form of scratches.

Entrance mats

A proper clean-off zone/mat is strongly recommended. It will reduce the soiling of the flooring by as much as 70%. Entrance mats, when properly serviced, can effectively remove abrasive materials from foot traffic and reduce the amount of transferred water. IVC recommends a minimum of two full strides of entrance matting. Where possible, prevent dirt from reaching the floor. A suitable barrier matting system will help prevent soiling and abrasive material from entering a building, assisting cleaning and maintenance.

Regularly clean the clean-off zone matting so that it functions optimally. Replace the clean-off mat when necessary..

Avoid rubber or latex backed mats, rubber furniture feet and castors, as these may leave permanent stains.

Important

- Take care to immediately wipe up any spillages on the vinyl flooring to minimize the risk of permanent staining occurring.
- Vinyl flooring can be slippery when wet.
- If the use of a neutral pH detergent is necessary then carefully follow the dilution recommendations of the manufacturer

- After cleaning, the floor should be dry within 1 or 2 minutes so there is no residual water with cleaning detergent and dirt remaining on the floor.

Protection of sliding furniture

Place good quality protective felt pads under chair and table legs. Furniture cups should be used to avoid high point loading

Regular cleaning

Remove daily dirt

- Sweeping
- Dry mopping
- Vacuum cleaning

Spot and stain removal

- Damp cloth
- Hand pad

Damp mopping

- Microfibre damp mop
- Traditional mop (as dry as possible)



Occasional cleaning

Mopping

- Damp mopping
- Traditional mopping (as dry as possible)

Combine machine

- Red scrub pad
- Neutral detergent

- Low amount of water!

Maintenance

Spray cleaning

- High-speed (450 rpm)
- Red drybuff pad
- Spray bottle with neutral detergent

Camouflage minor scratches

- High-speed (450 rpm)
- PU refresher
- Red drybuff pad
- Cotton cloths



Recommended maintenance products

Choose IVC Accessories's maintenance products, specially developed, and prolong the life of your IVC.
www.ivc-commercial.com

Important part from the warranty:

- Almost all flooring will vary in colour over time when exposed to UV light. Avoid this by using curtains or sunscreens when the sun is very bright.
- Avoid rubber or latex backed mats as they may leave stains. Also rubber and latex castors (we advise castors type 'W' in accordance with EN 12529) or protection caps under furniture cannot be used.
- Protect against scratching from furniture feet by using wide free-moving castors, glides, rollers or felt pads. Use furniture caps under heavy items or appliances to prevent indentation.
- In case of loose lay installation, damage of the vinyl flooring caused by heavy overload or sliding activities is not covered by the warranty conditions.
- Do not allow cigarettes, matches and other very hot items to contact the floor as this causes permanent damage.

Important: Cleaning or maintenance may only take place if the IVC are correctly installed and there are no visible imperfections.

Contact your IVC representative for the complete warranty conditions

March 2019