

# Vision

## Technical specifications

<b>European classification</b>	EN ISO 10874	23 - 33 - 41
<b>Total thickness, mm</b>	EN ISO 24346	2.20
<b>Wearlayer, mm</b>	EN ISO 24340	0.50
<b>Total weight, kg/m<sup>2</sup></b>	EN ISO 23997	2.00
<b>Available widths*, m</b>	EN ISO 24341	2 / 2.5 / 3 / 3.5 / 4
<b>Standard length, m</b>	EN ISO 24341	30
<b>Inflammability</b>	EN 13501-1	Bfl-S1
<b>Iaq</b>	Sanitary certificate	low VOC emissions
<b>Chips</b>		yes
<b>Acoustical insulation, dB</b>	EN ISO 4918	13
<b>Slip restraint</b>	DIN 51130	R10
<b>Residual indentation, mm</b>	EN ISO 24343-1	≤0.20
<b>Thermal resistance, m<sup>2</sup> K/W</b>	EN ISO 12664	0.0088
<b>Thermal conductivity, W/mK</b>	EN ISO 10456	0.25
<b>Residential warranty** (years)</b>		15
<b>Commercial warranty** (years)</b>		5

\* - On selected items, contact your IVC manager for detail.

\*\* - The warranty covers manufacturing defects and early wear due to normal residential use.